

Brilliant, consistent production color and customized output—including envelopes







A digital press for spectacular short-run, on-demand print jobs.

Your customers frequently ask you to print short-run quantities with variable data on a wide range of formats—including envelopes—in specific colors.

You need a reliable asset on the shop floor to handle that.

The new **OKI proColor**[™] **pro905DP** digital color press from Oki Data Americas, Inc. is the answer for spectacular color and great short-run performance. It features:

- High-capacity HD Color production printing
- PANTONE[®] calibrated
- Media flexibility and cost-efficiency

The pro905DP: the perfect combination of brawn and finesse.

OKI proColor™ pro905DP Highlights:

Single Pass Color™ digital technology—straight-through print path handles up to 300 gsm, tabloid-extra sheets (12" x 18"), and banners up to 4' long

High-productivity print speed—up to 36 ppm in Color and 40 ppm Monochrome¹

High Definition (HD) Color printing technology for increased color depth and richer hues—even on ordinary paper

1200 x 600 dpi print resolution for clear, sharp text and graphics

Designed for short-run production: High-Capacity Lift holds up to 4,000 sheets of 20 lb. bond paper

2-Year On-Site warranty² for low operating costs



² Available in the U.S. only.



High-capacity color printing

The OKI proColor" pro905DP is a color-matching digital printer from Oki Data Americas, Inc.—with a twist: it's also a short-run production press that handles tabloid-extra (12" x 18") sheets, a wide range of specialty and custom media, and many types of envelopes, like a dream.

While that means the pro905DP will help you cut on-demand jobs from hours to minutes, you still have to meet your customers' demands for vibrant and accurate color output. The pro905DP is the perfect solution for satisfying the needs of color-centric clientele.

The printer delivers consistent professional-quality color through OKI's HD Color printing technology, automatically calibrating colors, making color corrections on the fly, and supporting PANTONE®, SWOP®, Japan Color, Euroscale and custom ink simulations. That, and up to 1200 x 600 dpi resolution, enables the pro905DP to deliver fine details and stunning color depth, whether on glossy stock or even ordinary paper.

Media flexibility and cost-efficiency, too

The pro905DP Series is the ideal solution for producing a wide range of documents on a variety of paper weights and sizes. Single Pass Color™ technology and the straight-through paper path allow for faster color and monochrome print speeds, minimal paper jams, and smooth handling.

Features like Auto Media Detect automatically adjust the printer to your required media type, and Auto Color Balance ensures that output remains consistent from start to finish. And, with the cost of a black & white page on the pro905DP lower than typical office equipment, you can also use it for all of kinds of business documents, like annual reports, complete with variable data customization and full-color covers—on cover stock.

The answer to your shortrun color printing needs

The pro905DP from Oki Data Americas Inc.: high capacity and high quality—the right Digital Press for your demanding, color-sensitive short-run printing needs.



Single Pass Color[™] technology and straight-through paper path handles thick paper stock and banner sheets.






Print Quality Typefaces Compatibility	Print Speed¹ Time to 1st Page¹ Warm-up Time Processor Monthly Duty Cycle Resolution Color Matching Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	Letter/A4 – up to 36 ppm Color, 40 ppm Mono; Tabloid/A3 – up to 19 ppm Color, 21 ppm Mono 10.5 sec. Color, 9 sec. Mono 110 sec. or less from Power On 800 MHz PowerPC 750 Average: 5,000–15,000 pages; Max: 150,000 pages HD Color Technology: 1200 x 600 dpi Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9−10.5, OS X Intel 10.4.4−10.5 TCP/IP; NetWare®; EtherTalk Swatch Utility; PDF Direct Print (version 1.6 - Windows® environment only)
Typefaces	Warm-up Time Processor Monthly Duty Cycle Resolution Color Matching Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	110 sec. or less from Power On 800 MHz PowerPC 750 Average: 5,000–15,000 pages; Max: 150,000 pages HD Color Technology: 1200 x 600 dpi Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
Typefaces	Processor Monthly Duty Cycle Resolution Color Matching Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	800 MHz PowerPC 750 Average: 5,000–15,000 pages; Max: 150,000 pages HD Color Technology: 1200 x 600 dpi Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
Typefaces	Monthly Duty Cycle Resolution Color Matching Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	Average: 5,000–15,000 pages; Max: 150,000 pages HD Color Technology: 1200 x 600 dpi Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
Typefaces	Resolution Color Matching Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	HD Color Technology: 1200 x 600 dpi Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9-10.5, OS X Intel 10.4.4-10.5 TCP/IP; NetWare®; EtherTalk
Typefaces	Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	Color Matching software and Color Correct from Oki Printing Solutions; PS Gamma Adjuster; Supports color manageme systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9−10.5, OS X Intel 10.4.4−10.5 TCP/IP; NetWare®; EtherTalk
**	Printer Fonts Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	systems that utilizes ICC profiles; PANTONE® calibrated 86 scalable PCL® fonts; 10 TrueType® fonts; 136 Adobe® PostScript® Type 1 fonts; 1 bitmap font; OCR A/B; USPS barcode PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9−10.5, OS X Intel 10.4.4−10.5 TCP/IP; NetWare®; EtherTalk
**	Printer Languages Connectivity Operating Systems Network Protocols Included with Printer	PCL® 5c, PCL 6, Adobe PostScript 3™ Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9−10.5, OS X Intel 10.4.4−10.5 TCP/IP; NetWare®; EtherTalk
Compatibility	Connectivity Operating Systems Network Protocols Included with Printer	Hi-Speed USB 2.0 and 10 Base-T/100 Base-TX/1000 Base-T Ethernet with internal Web Server Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
	Operating Systems Network Protocols Included with Printer	Windows® 7, Vista® (32-/64-bit); XP Professional (32-/64 bit), XP Home; Server 2003 Standard/Enterprise/Datacenter Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
	Network Protocols Included with Printer	Editions; Server 2003 x64 (SP1); 2000 Professional (SP4 or later); 2000 Server (SP4 or later); 2000 Advanced Server (SP4 or later); Mac® OS X PowerPC 10.3.9–10.5, OS X Intel 10.4.4–10.5 TCP/IP; NetWare®; EtherTalk
	Included with Printer	
		Swatch Utility, DDE Direct Print (version 1.6. Windows® environment enly)
Utilities		Swatch dutity, For Direct Finit (version 1.0 - windows" environment Offty)
Memory	RAM (Standard and Max)	512 MB standard; Maximum of 1,024 MB
	Hard Disk Drive	40 GB Standard
Media Handling	Paper Capacity Tray 1	530 sheets
	Hopper-Capacity Lift	-4,000 sheets/envelopes
	Paper Sizes	Tabloid extra (12" x 18"), tabloid (11" x 17"), legal, letter, executive, 3" x 5" index cards, 4" x 6" and 5" x 7" photo pape A3, A4, A5, A6, B5, C5, DL, Com 10, Monarch envelopes, and banners (up to 12.9" x 47.24")
	Paper Weight	Trays 1 thru 5 – 17 lb. bond–80 lb. cover (64–216 gsm); Multi-purpose tray – 17 lb. bond–120 lb. cover (64–307 gsm); Duplex – 20 lb. bond–65 lb. cover (75–188 gsm) for letter and tabloid sheets
	Duplex (2-sided) Printing	Optional
	Paper Feeding	Auto Media Detect, Auto Paper Tray Select, Paper Empty Sensor, Paper Low Sensor
	Paper Output	500 sheets, face down; 200 sheets, face up
Environmental	Size (HxWxD)	Printer and Delivery Conveyor Belt: 112.0" x 24.6" x 50.5.2" (285 cm x 63 cm x 128.3 cm)
	Weight	Printer: 152 lb. (69.0 kg) with consumables
	Temperature/Humidity	Operating: 50°F to 89.6°F (10°C to 32°C), 20% to 80% RH; Storage: -4°F to 113°F (-20°C to 45°C), 10% to 90% RH
	Power Consumption	Operating – Typical 780W, Peak <1500W; Standby 200W (average); Power Save 33W
	Noise Level	Operating – 54dB(A) or less; Standby: 42dB(A) or less; Power Save: 28dB(A) (background level)
Warranty	Limited Warranty	Printer and Conveyor Belt: 2-Year On-Site ² ; 5-Year Digital LED Printheads
Product	Description	Part Numbers
pro905DP	Digital Color Press	120V - 91661901 230V - 91661902
Toner Cartridges	CMY: 16,500 pages ³ (Est. Life)	Cyan - 52124003 Magenta - 52124002 Yellow - 52124001
	Black: 18,500 pages ³ (Est. Life)	Black – 52124004
mage Drums	42,000 pages ⁴ (Estimated Life)	Cyan - 56125003 Magenta - 56125002 Yellow - 56125001 Black - 56125004
Transfer Belt	100,000 pages (Estimated Life)	42931602
Fuser Unit	100,000 pages (Estimated Life)	120V - 42931701 230V - 42931702
Waste Toner Box	30,000 pages (Estimated Life)	42869401
Huste Ionei DUA	¹ Published performance results based	² Available in the U.S. only. Important Consumables Information: This product has been designed and engineered to operate

Published performand on laboratory testing. Individual results may vary.

Important Consumables Information: This product has been designed and engineered to operate only with genuine Oki Data Americas, Inc. consumables. Use of non-genuine consumables will result in the loss of certain printer enhancements, such as Auto Color Balance and Toner Sensor gauge.

For more information on Digital Color Printers and Supplies from Oki Data Americas, Inc.: 1.800.OKI.DATA (800.654.3282).



Specifications are subject to change without notice.

Featured products may not be available in all countries. Please contact your local office for regional availability. © 2011 Oki Data Americas, Inc. OKI Reg. T.M., Reg. T.M., Oki Electric Industry Co., Ltd. HD Color logo T.M., Single Pass Color T.M., Oki Data Corp. proColor logo T.M., Oki Data Americas, Inc. PCL Reg. T.M., Hewlett Packard Co. Microsoft, Windows, Vista Reg. T.M., Microsoft Corp. PostScript Reg. T.M., PostScript 3 T.M., Adobe Systems, Inc. NetWare Reg. T.M., Novell Inc. Mac Reg. T.M., Apple Inc. PANTONE Reg. T.M. Pantone LLC OKI DATA AMERICAS, INC.

2000 BISHOPS GATE BLVD. Mount Laurel, NJ 08054-4620 Tel: 800.0KI.DATA (800.654.3282) Fax: 856.222.5320

www.okidata.com/procolor



² Available in the U.S. only. ³ Letter/A4 at 5% coverage. Ships with 7,500-page "starter"

toner cartridges. 4 Based on 500 pages/job.